

IN THE CLAIMS

*The status of the claims as presently amended is as follows:*

1. *(Currently Amended)* An image pickup apparatus comprising:

a taking lens;

a main body;

an image pickup device that receives light passing through said taking lens and outputs an image signal;

a photometric device that receives the light passing through said taking lens and outputs luminance information;

a control circuit that sets an exposure compensation value according to an output from said photometric device;

wherein said control circuit acquires information on characteristics of said taking lens from said taking lens and sets a first exposure compensation value according to the acquired information on characteristics of said taking lens and the luminance information outputted from said photometric device, to cause said image pickup device to carry out a first storage of the light passing through said taking lens, based on the set first exposure compensation value, and sets a second exposure compensation value according to a result of the first storage, to cause said image pickup device to carry out a second storage of the light passing through said taking lens, based on the set second exposure compensation value.

2. *(Currently Amended)* An image pickup apparatus as claimed in claim 1, wherein said taking lens is removably attached to said main body, ~~and said control circuit acquires information on characteristics of said taking lens from said taking lens and sets the exposure compensation value according to the luminance information outputted from said photometric device and the information on characteristics of said taking lens to cause said image pickup device to carry out the first storage.~~

3. *(Original)* An image pickup apparatus as claimed in claim 1, further comprising a mirror element, and wherein the light passing through said taking lens reaches said photometric device when said mirror element is in a first position, and the light passing through said taking lens does not reach said photometric device when said mirror element is in a second position.

4. (*Original*) An image pickup apparatus as claimed in claim 3, further comprising an eyepiece lens used in observing a subject by a user, and an optical element that divides the light passing through said taking lens into light reaching said photometric device and light reaching said eyepiece lens.

5. (*Previously Presented*) An image pickup apparatus as claimed in claim 1, wherein said photometric device outputs a plurality of pieces of luminance information for a plurality of areas into which a photographic screen is divided.

6. (*Currently Amended*) An image pickup apparatus as claimed in claim 1, wherein said first and second exposure compensation values each include at least one of a storage time ~~and~~ or an output amplification factor of said image pickup device, and said control circuit causes said image pickup device to carry out the first storage by changing one of the storage time ~~and~~ or the output amplification factor based on the first exposure compensation value, and causes said image pickup device to carry out the second storage by changing the one of the storage time and the output amplification factor based on the second exposure compensation value.

7-9. (*Canceled*)

10. (*Currently Amended*) A control method for an image pickup apparatus including a taking lens, a main body, an image pickup device that receives light passing through the taking lens and outputs an image signal, and a photometric device that receives the light passing through the taking lens and outputs luminance information, the control method comprising:

a photometric step of causing the photometric device to calculate field luminance information;

a first compensation step of acquiring information on characteristics of the taking lens from the taking lens and setting a first exposure compensation value ~~based on~~ according to the acquired information on characteristics of the taking lens and the field luminance information calculated in said photometric step;

a first storage step of causing the image pickup device to carry out a first storage of the light passing through the taking lens, based on the first exposure compensation value set in said first compensation step;

a second compensation step of setting a second exposure compensation value according to a result of the first storage carried out in said first storage step; and

a second storage step of causing the image pickup device to carry out a second storage of the light passing through the taking lens, based on the second exposure compensation value set in said second compensation step.

11. (*Currently Amended*) A control method as claimed in claim 10, wherein the taking lens is removably attached to the main body, ~~and in said first compensation step, information on characteristics of said taking lens is acquired from the taking lens and the exposure compensation value is set according to the information on characteristics of the taking lens and the luminance information.~~

12. (*Currently Amended*) A control method for an image pickup apparatus including a taking lens, an image pickup device, and a photometric device disposed at a location different from a location at which the image pickup device is disposed, the image pickup apparatus being ~~capable of switching switchable~~ between a state in which light passing through the taking lens is caused to reach the photometric device, and a state in which the light passing through the taking lens is not caused to reach the photometric device, the control method comprising:

a photometric step of causing the photometric device to determine field luminance information;

a first compensation step of acquiring information on characteristics of the taking lens from the taking lens and setting a first exposure compensation value ~~based on~~ according to the acquired information on characteristics of the taking lens and the field luminance information determined in said photometric step;

a first storage step of causing the image pickup device to carry out a first storage of the light passing through the taking lens, based on the first exposure compensation value set in said first compensation step;

a second compensation step of setting a second exposure compensation value according to a result of the first storage carried out in said first storage step; and

a second storage step of causing the image pickup device to carry out a second storage of the light passing through the taking lens, based on the second exposure compensation value set in said second compensation step.

13. (*Currently Amended*) A control method as claimed in claim 12, wherein the control method causes the light passing through the taking lens to reach only one of the image pickup device ~~and or~~ the photometric device.

14. (*Currently Amended*) A computer-readable storage medium storing a computer program for implementing a control method for an image pickup apparatus including a taking lens, a main body, an image pickup device that receives light passing through the taking lens and outputs an image signal, and a photometric device that receives the light passing through the taking lens and outputs luminance information, the computer program comprising:

a photometric module for causing the photometric device to calculate field luminance information;

a first compensation module for acquiring information on characteristics of the taking lens from the taking lens and setting a first exposure compensation value based on according to the acquired information on characteristics of the taking lens and the field luminance information calculated by said photometric module;

a first storage module for causing the image pickup device to carry out a first storage of the light passing through the taking lens, based on the first exposure compensation value set by said first compensation module;

a second compensation module for setting a second exposure compensation value according to a result of the first storage carried out by said first storage module; and

a second storage module for causing the image pickup device to carry out a second storage of the light passing through the taking lens, based on the second exposure compensation value set by said second compensation module.

15. (*Currently Amended*) A computer-readable storage medium storing a computer program for implementing a control method for an image pickup apparatus including a taking lens, an image pickup device, and a photometric device disposed at a location different from a location at which the image pickup device is disposed, the image pickup apparatus being ~~capable of switching~~ switchable between a state in which light passing through the taking lens is caused to reach the photometric device, and a state in which the light passing through the taking lens is not caused to reach the photometric device, the computer program comprising:

a photometric module for causing the photometric device to determine field luminance information;

a first compensation module for acquiring information on characteristics of the taking lens from the taking lens and setting a first exposure compensation value ~~based on~~ according to the information on characteristics of the taking lens and the field luminance information determined by said photometric module;

a first storage module for causing the image pickup device to carry out a first storage of the light passing through the taking lens, based on the first exposure compensation value set by said first compensation module;

a second compensation module for setting a second exposure compensation value according to a result of the first storage carried out by said first storage module; and

a second storage module for causing the image pickup device to carry out a second storage of the light passing through the taking lens, based on the second exposure compensation value set by said second compensation module.